



4050RLA®

STANDARD GRADE SIGN MAKER'S APPLICATION TAPE WITH RELEASE LINER ADHESION TECHNOLOGY

BACKING

A standard weight latex saturated paper designed specifically for premask, prespace and application tape requirements.

ADHESIVE

A natural latex adhesive with medium tack levels, which achieves transfer and premasking of mid-sized die cut or prespaced vinyl and printed graphics.

R TAPE RELEASE LINER ADHESION (RLA™) PERFORMANCE FEATURES

R Tape Premasks upgraded with RLA™ technology have improved adhesion to paper or film release liners, yet maintain the specified adhesion level to the vinyl or printed graphic. R Tape RLA Premasks anchor themselves to the release liner for superior lay flat to prevent tunneling and edge curling of stacked or rolled graphics. Some R Tape RLA products significantly reduce the need for heat and vacuum process after lamination.

Table with 2 columns: Physical Specifications and values. Rows include Adhesive (Natural Latex), Color (White/Translucent), Tape Thickness (microns) (100 - 113), *Adhesion to Steel (oz./in. width) (13 - 15), Tensile (lb./in.) (17), Elongation (3 - 4%), and Tear Resistance (grams) (50).

* Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.

APPLICATIONS

- Application tape for medium sized graphics.
• Premask for printed vinyl graphics.
• Clean transfer with wet application.
• All purpose transfer and prespace tape.

WARRANTY: TAPES ARE ONLY WARRANTED TO BE FREE OF DEFECTS IN WORKMANSHIP OR MATERIAL AT TIME OF SHIPMENT. MANUFACTURER WILL REPLACE OR CREDIT ANY MATERIAL MANUFACTURER DEEMS DEFECTIVE. NO ACCEPTANCE OR RESPONSIBILITY FOR LOSS, DAMAGE, OR EXPENSE, IMPLIED OR OTHERWISE, SHALL BE ASSUMED BY SELLER OR MANUFACTURER. USER ASSUMES ALL RISK AND LIABILITY IN CONNECTION HEREWITH.

R Tape Corporation

6 Ingersoll Rd, South Plainfield, NJ 07080

Phone: 908-753-5570

Fax: 908-753-5014

Toll Free: 1-800-440-1250

4050-RLA Spec Sheet/Issue #01/062299