



4075RLA®

**STANDARD GRADE SIGN MAKER'S APPLICATION TAPE
WITH RELEASE LINER ADHESION TECHNOLOGY**

BACKING

A standard weight saturated paper with high elongation, resistance to abrasion and moisture, with greater conformability to facilitate immediate placement and transfer of small to large graphics.

ADHESIVE

A natural rubber adhesive with high tack levels to achieve more consistent transfer of computerized vinyl graphics regardless of size and type. The stable adhesive system permits longer time periods between application of the tape and the actual transfer.

R TAPE RELEASE LINER ADHESION (RLA™) PERFORMANCE FEATURES

R Tape Premasks upgraded with RLA™ technology have improved adhesion to paper or film release liners, yet maintain the specified adhesion level to the vinyl or printed graphic. R Tape RLA™ Premasks anchor themselves to the release liner for superior lay flat to prevent tunneling and edge curling of stacked or rolled graphics.

PHYSICAL SPECIFICATIONS	
Adhesive	Natural Rubber
Color	White/Translucent
Tape Thickness (mils)	4.0 – 4.5
*Adhesion to Steel (oz./in. width)	16 – 18
Tensile (lb./in.)	17
Elongation	3 – 4%
Tear Resistance (grams)	50

** Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.*

APPLICATIONS

High adhesion level combined with the high tensile, elongation and tear resistant paper provides the sign maker and decal manufacturer with the best possible combination of application tape and pre-space tape. Plus, the ability to store or roll finished graphics without the lifting or tunneling of tape from liner.

WARRANTY: TAPES ARE ONLY WARRANTED TO BE FREE OF DEFECTS IN WORKMANSHIP OR MATERIAL AT TIME OF SHIPMENT. MANUFACTURER WILL REPLACE OR CREDIT ANY MATERIAL MANUFACTURER DEEMS DEFECTIVE. NO ACCEPTANCE OR RESPONSIBILITY FOR LOSS, DAMAGE, OR EXPENSE, IMPLIED OR OTHERWISE, SHALL BE ASSUMED BY SELLER OR MANUFACTURER. USER ASSUMES ALL RISK AND LIABILITY IN CONNECTION HEREWITH.

R Tape Corporation

6 Ingersoll Rd, South Plainfield, NJ 07080

Phone: 908-753-5570

Fax: 908-753-5014

Toll Free: 1-800-440-1250

4075RLA Spec Sheet/Issue #01/06-01-00